

Lieferprogramm
EN 10305-4 – nahtlos, kalt gezogene Präzisionsstahlrohre (HPL)

| | 0,50 | 0,75 | 1,00 | 1,50 | 2,00 | 2,25 | 2,50 | 3,00 | 3,50 | 4,00 | 4,50 | 5,00 | 6,00 | 8,00 | 9,00 | 10,00 | |
|----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|----|
| 4 | s | s | s/v | | | | | | | | | | | | | | 4 |
| 5 | | s | s/v | | | | | | | | | | | | | | 5 |
| 6 | | s | s/v | s/v | s/v | s | | | | | | | | | | | 6 |
| 8 | | | s/v | s/v | s/v | | | | | | | | | | | | 8 |
| 10 | | | s/v | s/v | s/v | | s/v | | | | | | | | | | 10 |
| 12 | | | s/v | s/v | s/v | | s/v | s/v | | | | | | | | | 12 |
| 14 | | | s/v | s/v | s/v | | s/v | s/v | s | | | | | | | | 14 |
| 15 | | | s/v | s/v | s/v | | s/v | s/v | | | | | | | | | 15 |
| 16 | | | s/v | s/v | s/v | | s/v | s/v | | | | | | | | | 16 |
| 20 | | | s/v | s/v | s/v | | s/v | s/v | s/v | s | | | | | | | 20 |
| 22 | | | s/v | s/v | s/v | | s/v | s/v | s/v | s | | | | | | | 22 |
| 25 | | | s | s/v | s/v | | s/v | s/v | s/v | s/v | s | s | | | | | 25 |
| 28 | | | | s/v | s/v | | s/v | s/v | s/v | s/v | s | s | | | | | 28 |
| 30 | | | | | s/v | | s/v | s/v | s/v | s/v | s | s/v | s | | | | 30 |
| 35 | | | | | s/v | | s/v | s/v | s/v | s/v | s | s/v | s/v | | | | 35 |
| 38 | | | | | s/v | | s | s/v | s | s/v | s | s/v | s | | | | 38 |
| 42 | | | | | s/v | | | s/v | | s/v | | | | | | | 42 |
| 50 | | | | | | | | | | | | | s | | s | | 50 |
| 65 | | | | | | | | | | | | | | s | | | 65 |
| 80 | | | | | | | | | | | | | | | | s | 80 |

s= schwarz, v = verzinkt

Weitere Dimensionen auf Anfrage!